

# Mosaic Carbon

## Mosaic Carbon Black

| CATEGORY           | VALUE                          | CATEGORY               | VALUE                      |
|--------------------|--------------------------------|------------------------|----------------------------|
| Top Coating        | PLATICOAT™                     | Temperature Resistance | -40°C-120°C<br>-40°F-248°F |
| Base Film Type     | Polycaprolactone Aliphatic TPU | Initial Peel Adhesion  | 23N/in                     |
| Adhesive Type      | Repositionable Acrylic PSA     | Elongation At Break    | 304%                       |
| Self-Healing       | PASS                           | 60° Surface Gloss      | 38                         |
| Film Thickness     | 8mil                           | UV Test                | 5000 Hours Pass            |
| Film Specification | 60in × 50ft                    | Chemical Resistance    | No Harm                    |
| Warranty           | 10 Years                       | Anti Rock Chips Test   | PASS                       |

\*The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

\*The above data is used as a reference for material selection, but does not constitute a guarantee.

\*The company has the right to modify the relevant technical data without prior notice.



Easy Installation



Stain Resistance



Optical Clarity High Gloss



Self-Healing



10-Year Warranty

# Mosaic Carbon

## Mosaic Carbon Clear

| CATEGORY           | VALUE                          | CATEGORY               | VALUE                      |
|--------------------|--------------------------------|------------------------|----------------------------|
| Top Coating        | PLATICOAT™                     | Temperature Resistance | -40°C-120°C<br>-40°F-248°F |
| Base Film Type     | Polycaprolactone Aliphatic TPU | Initial Peel Adhesion  | 11N/in                     |
| Adhesive Type      | Repositionable Acrylic PSA     | Elongation At Break    | 327%                       |
| Self-Healing       | PASS                           | 60° Surface Gloss      | 22                         |
| Film Thickness     | 8mil                           | UV Test                | 5000 Hours Pass            |
| Film Specification | 60in × 50ft                    | Chemical Resistance    | No Harm                    |
| Warranty           | 10 Years                       | Anti Rock Chips Test   | PASS                       |

\*The product of different color may vary in thickness, depending on the actual situation. If you have any inquiry, feel free to contact us.

\*The above data is used as a reference for material selection, but does not constitute a guarantee.

\*The company has the right to modify the relevant technical data without prior notice.



Easy Installation



Stain Resistance



Optical Clarity High Gloss



Self-Healing



10-Year Warranty